



The MSDS format adheres to the standards and regulatory requirements of the United States and may not meet regulatory requirements in other countries.

DuPont  
Material Safety Data Sheet

Page 1

-----  
"DELRIN" ACETAL RESIN ON SYNONYM LIST DEL011  
DEL011 Revised 23-AUG-2006  
-----

-----  
CHEMICAL PRODUCT/COMPANY IDENTIFICATION  
-----

Material Identification

"DELRIN" is a registered trademark of DuPont.

Tradenames and Synonyms

"DELRIN" 510GR BL1080,  
"DELRIN" 510GR NC000,  
"DELRIN" 525GR NC000,  
"DELRIN" 570 NC000;  
"DELRIN" DE9036 NCB000,  
"DELRIN" DE9191 NC000,  
"DELRIN" DE9191X NC000,  
"DELRIN" DE9255 NC000,  
"DELRIN" DE9453 BL1080,  
"DELRIN" DE9453 BL1083,  
"DELRIN" DE9453 BLN1080,  
"DELRIN" DE9453 NC000,  
"DELRIN" DE9453 YL1063,  
"DELRIN" DE9454 NC000,  
"DELRIN" DE9474 BL1080,  
"DELRIN" DE9474 BLN1080,  
"DELRIN" DE20050 NC000

Company Identification

MANUFACTURER/DISTRIBUTOR

DuPont Engineering Polymers  
1007 Market Street  
Wilmington, DE 19898

PHONE NUMBERS

Product Information : 1-(800)-441-7515  
Transport Emergency : 1-(800)-424-9300  
Medical Emergency : 1-(800)-441-3637

-----  
COMPOSITION/INFORMATION ON INGREDIENTS  
-----

Components

Material	CAS Number	%
ACETAL POLYMER		>70
STABILIZER		<2
PIGMENT		<1
FIBERGLASS		<30
FORMALDEHYDE	50-00-0	<0.005

## (COMPOSITION/INFORMATION ON INGREDIENTS - Continued)

## Components (Remarks)

Material is not known to contain Toxic Chemicals under Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

Additives in this product do not present a respiration hazard unless the product is ground to a powder of respirable size and the dust is inhaled. All dusts are potentially injurious to the respiratory tract if respirable particles are generated and inhaled in sufficiently high concentrations. Good industrial hygiene practices, as with all dusts, should include precautions to prevent inhalation of respirable particles.

-----  
HAZARDS IDENTIFICATION  
-----

## Potential Health Effects

## ADDITIONAL HEALTH EFFECTS

Read the specific datasheet for product to be used before using this resin, as well as the Delrin Molding Guide.

## ACETAL POLYMER

There are no known effects from exposure to the Delrin polymer itself. If overheated, the polymer releases formaldehyde which may cause skin, eye, and respiratory irritation and allergic reactions.

Significant skin permeation and systemic toxicity after contact appears unlikely. There are inconclusive or unverified reports of human sensitization.

## FIBERGLASS

The mechanical action of the sharp fibers from Fiber Glass may cause skin irritation with discomfort or rash.

Eye contact with Fiber Glass particles may cause mechanical eye irritation with discomfort, tearing, or blurring of vision.

Inhalation of Fiber Glass particles may cause irritation of the upper respiratory passages, with coughing and discomfort.

Results from epidemiology studies suggest no causal relationship between Fiber Glass exposure and cancer. One epidemiology study does indicate a slight increase in lung cancer deaths. The evidence that fiber glass is related to these increased lung cancer deaths is considered weak.

## (HAZARDS IDENTIFICATION - Continued)

Individuals with preexisting diseases of the lungs may have increased susceptibility to the toxicity of excessive exposures.

## # Carcinogenicity Information

The following components are listed by IARC, NTP, OSHA or ACGIH as carcinogens.

Material	IARC	NTP	OSHA	ACGIH
FORMALDEHYDE	1	X	X	A2

-----  
FIRST AID MEASURES  
-----

## First Aid

## INHALATION

No specific intervention is indicated as the compound is not likely to be hazardous by inhalation. Consult a physician if necessary. If exposed to fumes from overheating or combustion, move to fresh air. Consult a physician if symptoms persist.

## SKIN CONTACT

The compound is not likely to be hazardous by skin contact, but cleansing the skin after use is advisable. If molten polymer gets on skin, cool rapidly with cold water. Do not attempt to peel polymer from skin. Obtain medical treatment for thermal burn.

## EYE CONTACT

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

## INGESTION

No specific intervention is indicated as compound is not likely to be hazardous by ingestion.

-----  
FIRE FIGHTING MEASURES  
-----

## Flammable Properties

Flash Point : Not Applicable

"Delrin" dust cloud ignition temperature is 440 degrees C (824 degrees F).

## Fire and Explosion Hazards:

Like most organic materials in powder form, dust generated from this product may form a flammable dust-air mixture. Potential for a dust explosion may exist. Minimize the generation and accumulation of dust. Keep away from sources of ignition. Burns with invisible flame. Hazardous gases/vapors produced in fire are carbon monoxide, formaldehyde.

## (FIRE FIGHTING MEASURES - Continued)

## Extinguishing Media

Water, Foam, Dry Chemical, CO2.

## Fire Fighting Instructions

Keep personnel removed and upwind of fire. Wear self-contained breathing apparatus.

-----  
ACCIDENTAL RELEASE MEASURES  
-----

## Safeguards (Personnel)

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

## Spill Clean Up

Spilled material is a slipping hazard.

Sweep up to avoid slipping hazard.

-----  
HANDLING AND STORAGE  
-----

## Handling (Personnel)

See FIRST AID and PERSONAL PROTECTIVE EQUIPMENT SECTIONS.

## Handling (Physical Aspects)

Open container only in well-ventilated area.

Minimize the generation and accumulation of dust.

## Storage

Store in a well ventilated area away from heat and sunlight.

Keep container closed to prevent contamination.

-----  
EXPOSURE CONTROLS/PERSONAL PROTECTION  
-----

## Engineering Controls

VENTILATION When hot processing this material, use local and/or general exhaust ventilation to control the concentration of vapors and fumes below exposure limits.

In cutting or grinding operations with this material, use local exhaust to control the concentration of dust below exposure limits.

## (EXPOSURE CONTROLS/PERSONAL PROTECTION - Continued)

## Personal Protective Equipment

## Eye/Face Protection

Wear safety glasses. Wear coverall chemical splash goggles and face shield when possibility exists for eye or face contact due to splashing or spraying of molten material. A full face mask positive-pressure air-supplied respirator provides protection from eye irritation.

## Respirators

When temperatures exceed 230 degrees C and ventilation is inadequate to maintain concentrations below exposure limits, use a positive-pressure air-supplied respirator. Air-purifying respirators may not provide adequate protection.

During grinding, sawing, routing, drilling or sanding operations use a NIOSH/MSHA approved air-purifying respirator with dust/mist cartridge or canister if airborne particulate concentrations are expected to exceed permissible exposure levels.

## Protective Clothing

If there is potential contact with hot/molten material, wear heat resistant clothing and footwear.

Wear leather or cotton gloves when grinding, sawing, routing, drilling or sanding.

## Exposure Guidelines

## Exposure Limits

"DELTRIN" ACETAL RESIN ON SYNONYM LIST DEL011

PEL (OSHA) : Particulates (Not Otherwise Regulated)  
15 mg/m<sup>3</sup>, 8 Hr. TWA, total dust  
5 mg/m<sup>3</sup>, 8 Hr. TWA, respirable dust

## Other Applicable Exposure Limits

## FIBERGLASS

PEL (OSHA) : None Established  
TLV (ACGIH) : 5 mg/m<sup>3</sup>, 8 Hr. TWA, inhalable particulate  
A4  
AEL \* (DuPont) : 5 mg/m<sup>3</sup> total dust - 8 Hr. TWA, non-  
respirable fiber (> 3 microns in  
diameter) non-fibrous particulate.

## FORMALDEHYDE

## (Other Applicable Exposure Limits - Continued)

PEL (OSHA)	:	0.75 ppm, 0.92 mg/m <sup>3</sup> , 8 Hr. TWA STEL 2 ppm, 2.5 mg/m <sup>3</sup>
TLV (ACGIH)	:	Ceiling 0.3 ppm, A2 Sensitizer
AEL * (DuPont)	:	0.5 ppm, 8 & 12 Hr. TWA 1 ppm, 15 minute TWA

\* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

-----  
PHYSICAL AND CHEMICAL PROPERTIES  
-----

## Physical Data

Melting Point	:	175-183 C (347-361 F)
Solubility in Water	:	Insoluble
Odor	:	Slight formaldehyde
Color	:	Pigmented.
Form	:	Pellets
Specific Gravity	:	>1

-----  
STABILITY AND REACTIVITY  
-----

## Chemical Stability

Stable at normal temperatures and storage conditions.

## Conditions to Avoid

Maintain polymer melt temperatures below 230 C (446 F) . Avoid prolonged exposure at or above the recommended processing temperatures.

## Incompatibility with Other Materials

Incompatible with strong acids and bases (decomposes forming formaldehyde) and strong oxidizing agents. At melt temperatures, acetal resins are incompatible with halogenated polymers such as PVC and PVDC and any elastomers containing halogenated polymers. Even small amounts of such contaminants can cause sudden and spontaneous formaldehyde gas formation. Workplace fume concentrations well above threshold levels are a likely result. Unsafe pressurization of equipment, e.g., extruders, molds, can also result.

Do not contaminate either virgin resin or rework. Do not mix this resin with pigments or additives other than those designated by DuPont. Do not mix this grade with other grades of Delrin, nor with any other resins, without first consulting DuPont. Doing any of the above may change the thermal stability of this resin and potentially cause decomposition.

## (STABILITY AND REACTIVITY - Continued)

## Decomposition

Decomposition of this material depends on the length of time it is exposed to elevated temperatures. At the recommended processing temperature of 210-220 C (410-428 F), decomposition should not be significant until after 30 minutes. Decomposition may be accelerated by contaminants, pigments, and/or other additives.

Autoclaving with pressurized steam may lead to a rapid decomposition and should be done for only minimum amounts of time. COOL COMPLETELY BEFORE OPENING the autoclave.

Hazardous gas/vapor produced is formaldehyde.

## Polymerization

Polymerization will not occur.

-----  
TOXICOLOGICAL INFORMATION  
-----

## Animal Data

## Delrin

Inhalation 6 hour LC50: > 22,000 mg/m3 in rats  
Oral LD50: > 11,000 mg/kg in rats

Delrin is not a skin irritant, and is not a skin sensitizer in animals.

Single or repeated inhalation exposures to high concentrations of Delrin dust resulted in collapse of some areas of the lungs, other areas were over-inflated. This effect was seen as late as 11-19 days post-exposure.

No toxic effect were observed in animals ingesting Delrin.

No animal test reports are available to define carcinogenic, mutagenic, developmental, or reproductive hazards.

## Fiber Glass

Skin irritation and mild eye irritation occurs in animals, but these effects are attributed primarily to mechanical damage rather than a chemical effect.

The effects in mice from single exposure by intratracheal instillation with Fiber Glass include an inflammatory response. Repeated inhalation exposures invoked pulmonary macrophage reactions similar to biologically inert dusts.

## (TOXICOLOGICAL INFORMATION - Continued)

Tests in some animals with Fiber Glass demonstrate carcinogenic activity. However, these studies were by artificial implantation or injection of fine glass fibers into the chest, abdominal cavity, or trachea and are judged to be irrelevant to industrial exposure. Chronic inhalation exposure of animals to fiber glass at low concentrations produced minimal fibrosis in one study and no adverse effects in a different study.

No animal test reports are available to define mutagenic, developmental, or reproductive hazards.

-----  
ECOLOGICAL INFORMATION  
-----

## Ecotoxicological Information

## AQUATIC TOXICITY:

No information is available. Toxicity is expected to be low based on insolubility in water. Do not discharge to streams, ponds, lakes or sewers.

-----  
DISPOSAL CONSIDERATIONS  
-----

## Waste Disposal

Preferred options for disposal are (1) recycling, (2) incineration with energy recovery, and (3) landfill. The high fuel value of this product makes option 2 very desirable for material that cannot be recycled, but incinerator must be capable of scrubbing out acidic combustion products. Treatment, storage, transportation, and disposal must be in accordance with applicable federal, state/provincial, and local regulations.

-----  
TRANSPORTATION INFORMATION  
-----

## Shipping Information

Not regulated in transportation by DOT/IMO/IATA.

-----  
REGULATORY INFORMATION  
-----

## U.S. Federal Regulations

TSCA Inventory Status : In compliance with TSCA Inventory requirements for commercial purposes.

## State Regulations (U.S.)

STATE RIGHT-TO-KNOW



## (REGULATORY INFORMATION - Continued)

No substances on the state hazardous substances list, for the states indicated below, are used in the manufacture of products on this Material Safety Data Sheet, with the exceptions indicated.

SUBSTANCES ON THE PENNSYLVANIA HAZARDOUS SUBSTANCES LIST PRESENT AT A CONCENTRATION OF 1 % OR MORE (0.01% FOR SPECIAL HAZARDOUS SUBSTANCES)- None known.

WARNING - SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM- Formaldehyde.

SUBSTANCES ON THE NEW JERSEY WORKPLACE HAZARDOUS SUBSTANCE LIST PRESENT AT A CONCENTRATION OF 1% OR MORE (0.1% FOR SUBSTANCES IDENTIFIED AS CARCINOGENS, MUTAGENS OR TERATOGENS)- None known.

-----  
OTHER INFORMATION-----  
Additional Information

MEDICAL USE: CAUTION: Do not use in medical applications involving permanent implantation in the human body. For other medical applications see DuPont CAUTION Bulletin No. H-50102.

-----  
The data in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

Responsibility for MSDS : REGULATORY AFFAIRS  
DUPONT ENGINEERING POLYMERS  
Address : CHESTNUT RUN PLAZA 713  
WILMINGTON, DE 19880-0713  
Telephone : 302-999-4257

# Indicates updated section.

This information is based upon technical information believed to be reliable. It is subject to revision as additional knowledge and experience is gained.

End of MSDS